

# Safety Data Sheet

**SDS No.:** 413

**HMIS** 

1

0

0

Sec. 8

Н

F

R

**PPE** 

JPS Composite Materials Corp. Acrylic Coated Aramid Fabric

Date of Preparation: 04/01/05 Revision: 2/3/21

## **SECTION 1: CHEMICAL PRODUCT & COMPANY IDENTIFICATION**

PRODUCT/CHEMICAL NAME: Aramid Coated with an Acrylic Copolymer

FINISH TYPES: Acrylic Coated Aramid APPLICATION: Industrial Applications

OTHER DESIGNATIONS: Woven Aramid (Kevlar® or Twaron®) Fabric

**COMPANY:** JPS Composite Materials

2200 S. Murray Ave., P.O. Box 2627, Anderson, SC 29624

**PRODUCT INFORMATION:** 1-800-288-0577 (8 am. to 5 pm Eastern Standard Time)

**EMERGENCY PHONE**: 1-800-288-0577

## **SECTION 2: HAZARD IDENTIFICATION**

\*\*\*\*\*\*\*EMERGENCY OVERVIEW\*\*\*\*\*\*

JPS Composite Materials Corp. coated and finished fabrics are stable under normal ambient conditions

#### **Potential Health Effects**

**Appearance and Odor:** Gold to yellow fibers woven into fabrics of varying weight and thickness, depending on the fabric weave style.

**Statement of Hazard:** Warning! This may cause temporary mechanical irritation of the eyes, skin, or upper respiratory tract. Dust or particulate from machining, grinding, or sawing the cured product may cause skin, eye, and upper respiratory irritation and possible dermatitis.

Primary Entry Routes:Eyes—YesSkin—YesInhalation—YesIngestion—NoHMIS® Rating:Health—1Flammability—0Reactivity—0Special—None

**Potential Health Effects:** 

**Eye:** Contact may cause mechanical irritation to the eyes. Dust or particulate from machining, grinding, or sawing the cured product may cause mechanical irritation.

**Skin:** Contact may cause mechanical irritation to the skin and possible dermatitis at clothing contact pressure points such as cuffs or collars. Duct or particulate from machining, grinding, or sawing the cured product may cause mechanical irritation and possible dermatitis.

**Inhalation:** May cause mechanical irritation to the upper respiratory tract. Dust or particulate from machining, grinding, or sawing the cured product may cause mechanical irritation to the upper respiratory tract.

**Ingestion:** Very unlikely. If a large amount of the product or the dust or particulate from the machining, grinding, or sawing the cured is swallowed, seek medical attention immediately.

**Medical Conditions Aggravated by Exposure:** Pre-existing conditions, such as respiratory or skin disorders, may be aggravated by exposure to the product or to the dust or particulate from machining, grinding, or sawing the cured product.

**Carcinogenic Information:** None of the finish components present in this material at concentrations equal to or greater than 0.1% are listed or regulated by NTP, OSHA, or ACGIH® as a carcinogen. Glass filament is listed by IARC as Group 3 (not classifiable as to a human carcinogen).

Other: OSHA (PEL) ACGIH (TLV)

Exposure limits for cured product 15 mg/m3 (Total) 10 mg/m3 (Inhalable) dust as [Particulate Not Otherwise 5 mg/m3 (Respirable) 3 mg/m3 (Respirable)

Regulated (PNOR) by OSHA or Classified (PNOC) by ACGIH]:

GHS Label: None

## **SECTION 3: INFORMATION ON INGREDIENTS**

Ingredient Name	CAS Number	% wt or % vol
Poly(terephthaloyl-chloride/p- phenylene-diamine) fiber	26125-61-1	50-80%
Acrylic Copolymer	N/A	20-50%

Trace Impurities: N/A

Ingredient	OSHA PEL	ACGIH TLV
Poly(terephthaloyl-chloride/p- phenylene-diamine) fiber	15 mg/m³ (Total) 5 mg/m³ (Respirable)	10 mg/m³ (Inhalable) 3 mg/m³ (Respirable)
Acrylic Copolymer	N/E	N/E

This product is not classified as a Hazardous Chemical as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

The percentage will vary depending on the fabric style and the individual component variation.

Where specific exposure limits for component dusts are not established, the levels provided for (Total/Inhalable) dust and (Respirable) fraction reflect the classification of Particulate Not Otherwise Regulated (PNOR) by OSHA or Classified (PNOC) by ACGIH®.

## **SECTION 4: FIRST AID MEASURES**

**Eye**: In case of contact with the product, the vapor or fumes generated from heating the product or the dust or particulate from machining, grinding, or sawing the cured product, immediately flush eyes with large amounts of water for at least 15 minutes, keeping the eyelids open. Get medical attention immediately.

**Skin:** In case of contact with the product or the dust or particulate, from machining, grinding, or sawing the cured product, immediately wash skin with a mild soap and room temperature to cool running water. Use a washcloth to help remove the dust or particulate. To avoid further irritation, do not rub or scratch irritated areas. Rubbing or scratching may force the dust or particulate into skin. Get medical attention immediately if the irritation persists.

**Inhalation:** If excessive inhalation of vapor, fumes, dust, or particulate from the product occurs, remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, qualified personnel may administer oxygen. Get medical attention immediately. Ingestion: Ingestion of the product or the dust or particulate from it is unlikely. If swallowed, get medical attention immediately.

After first aid, get appropriate in-plant, paramedic, or community medical support.

#### **SECTION 5: FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Use water spray, dry chemical or CO2 to extinguish fires.

**PROTECTIVE EQUIPMENT:**Because fire may produce toxic thermal decomposition products, wear a self-

contained breathing apparatus (SCBA) with a full face-piece operated in

pressure-demand or positive-pressure mode.

HAZARDOUS COMBUSTION PRODUCTS: Any sizing, binders or coatings on the fiberglass fabric might form hazardous

decomposition products during a sustained fire. Follow fire-fighting

procedures and use proper fire-fighting equipment

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

**En**sure cleanup is done only by trained personnel wearing appropriate personal protective equipment. Do not release runoff from fire control methods to sewers or waterways.

**Procedures in case of Accidental Release or Leakage:** Avoid contact with skin, eyes or clothing (See Section 8). Clean up material, put into a suitable container and dispose of properly (See Section 13).

# **SECTION 7: HANDLING & STORAGE**

**Handling:** Handle properly to prevent the spread of fiberglass dust or fibers.

**Storage:** Store in proper containers to prevent the spread of dusts and fibers. Low

humidity levels will increase the spread of dusts and fibers.

Precautions to be taken in Handling and Storage:

Store in a cool, dry place. Maintain sealed against contamination from dirt and moisture. Aramid fibers or fabric will be degraded by ultraviolet sunlight and discolored by fluorescent lighting. Keep away from food and drink. Avoid inhalation of filament or dust particulates generated during process operation.

**Regulatory Requirements:** 

Keep airborne dust and fiber concentrations below regulatory levels.

## SECTION 8: EXPOSURE CONTROLS & PERSONAL PROTECTIVE EQUIPMENT

**Eye/Face Protection:** Avoid eye and skin contact. Wear coverall goggles, as necessary, to prevent irritation, if airborne dust, fibers or particulate are present. Wear safety glasses with side shields, as necessary, if airborne dust, fibers or particulates are present when machining, grinding or sawing the cured product.

**Skin Protection**: Wear protective clothing such as a loose fitting, long sleeved shirt that covers to the base of the neck, long pants and gloves, as necessary, to prevent irritation. Skin irritation is known to occur primarily at pressure points such as around the neck, wrist, waist, and between fingers.

**Respiratory Protection:** Not ordinarily required. If sufficient dust, fibers or particulate are generated during use of the product or when machining, grinding or sawing the cured product, use a NIOSH approved dust respirator.

**Ventilation:** Use local exhaust sufficient to control dust, fibers or particulates generated. If exhaust ventilation is not available or is inadequate, use a NIOSH approved dust respirator.

**General Hygiene Recommendations:** Before eating, drinking, smoking or using toilet facilities, wash face and hands thoroughly with soap and water. Remove any contaminated clothing and launder before reuse. Use vacuum equipment to remove fibers, dust or particulates from clothing and work areas. Compressed air is not recommended.

## **SECTION 9: PHYSICAL & CHEMICAL PROPERTIES**

**Appearance and Odor:** Gold to Yellow Fibers woven into fabrics of varying weight and thickness, depending on the fabric weave.

Melting Point (°F/°C) ....... Aramid: Does not melt, will start carbonize at 800°F/>427°C

## **SECTION 10: STABILITY & REACTIVITY**

**Stability:** Stable under proper handling and storage conditions.

Incompatible Materials: None

Products evolved from Heat of Combustion or The products of combustion and decomposition depend on other materials present in the fire and the actual conditions of the fire. Burning will produce carbon and nitrogen oxides, small amounts of hydrogen cyanide, ammonia, aldehydes, aliphatic hydrocarbons, alcohol, organic acids and other unidentified gases and vapors that may be toxic. Avoid inhalation.

Hazardous Polymerization: Will not occur under proper conditions of use. Rapid heating of the product in bulk may produce an uncontrolled exothermic reaction that may char and decompose the finish, generating unidentified gases and vapors that may be toxic. Avoid inhalation.

# **SECTION 11: TOXICOLOGICAL INFORMATION**

 Skin ....... Aramid Fabric: Possible mechanical irritation

Eyes...... Aramid Fabric: Possible slight mechanical irritation

Inhalation... Aramid Fabric: Possible mild mechanical irritation

#### **SECTION 12: ECOLOGICAL INFORMATION**

## **Component Ecological Data:**

Aramid Fibers.....Essentially non-biodegradable; do not leach, material toxic to flora or fauna Finishes...Not inhibitory or toxic to microbes commonly found in biological treatment systems: are biodegradable; none appear to enhance foaming; discharge of scoured finishes should not result in increased effluent toxicity.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

Comply with Federal, State and Local regulation concerning health and environment when disposing of materials.

Waste Disposal Methods: Material for disposal should be placed in appropriate sealed containers to avoid potential human and environmental exposure. It is the responsibility of the generator to comply with all federal, state, provincial; and local laws and regulations. We recommend that you contact an appropriate waste disposal contractor and environmental agency for relevant laws and regulations. Under the U.S. Resource Conservation and Recovery Act (RCRA), it is the responsibility of the user of the product to determine at the time of disposal, whether the product meets relevant waste classification.

#### **SECTION 14: TRANSPORT INFORMATION**

DOT:

#### **SECTION 15: REGULATORY INFORMATION**

SARA Title III: Section 302/304 Extremely Hazardous Substance: None

Section 311 Hazardous Categorization: None

Section 313 Toxic Chemicals: None

**CERCLA Section 102** 

(A) Hazardous Substance: None

**RCRA Information:** Currently, this product is not listed in federal hazardous waste regulations 40 CFR, Part

261.33, paragraphs (e) or (f), i.e. chemical products that are considered hazardous if they become wastes. State or local hazardous waste regulations may also apply if they are different from the federal regulation. It is the responsibility of the user of the product to determine at the time if disposal, whether the product meets relevant waste

classification and to assure proper disposal.

WHMIS (Canada): Classification: None "This product has been classified in accordance with hazard criteria of the

"Controlled Products Regulations" and this SDS contains all the information required by

the "Controlled Products Regulations."

Ingredient Disclosure List: None

California Safe Drinking
Water and Toxic Enforcement
Act of 1986 (Proposition 65):

Warning! The state of California has determined that the following listed component

chemicals in this product may cause cancer and/or reproductive toxicity: None

U.S., EPA. TSCA Information: This product is an article as defined by TSCA and is not required to be listed in the TSCA

Inventory.

**Ozone Depletion Information:** 

This product does not contain or is not manufactured with ozone depleting substances as identified in Title VI, Clean Air Act "Stratospheric Ozone Protection" and the regulations set forth in 40CFR, Part 82.

#### **SECTION 16: OTHER INFORMATION**

**Explanation and Disclaimer:** Wherever such words or phrases as "hazardous," "toxic," "carcinogen," etc. appear herein, they are used as defined or described under state employee right-to-know laws, Federal OSHA laws or the direct sources for these laws such as the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), etc. The use of such words or phrases should not be taken to mean that we deem or imply any substance or exposure to be toxic, hazardous or otherwise harmful

Any exposure can only be understood within the entire context of its occurrence, which includes such factors as the substance's characteristics as defined in the SDS, amount and duration of exposures, other chemicals present and pre-existing individual differences in response to the exposure.

The data provided in this SDS is based on the information received from our raw material suppliers and other sources believed to be reliable. We are supplying you this data solely in compliance with the Federal OSHA Hazard Communication Standard, 29 CFR 1910.1200 and other Federal and state laws as described in Section 15: Regulatory Information.

The information contained in this SDS is proprietary and confidential to JPS Composite Materials. This SDS and the information in it are not to be used for purposes other than compliance with the Federal OSHA Hazard Communication Standard. If you have received this SDS from any other source than JPS Composite Materials or its authorized agent, the information contained in it may have been modified from the original document and it may not be the most current revision.

**Disclaimer**: The information provided herein is believed to be accurate but is not warranted. Much of the information contained in the Safety Data Sheet originates from suppliers; this information cannot be warranted by JPS Composite Materials Corp. to be correct or appropriate for the recipient's use. Recipients are advised to confirm in advance of need that the information is correct, applicable, and suitable to their circumstances. JPS Composite Materials Corp. assumes no legal responsibility for the use or reliance on the data in this SDS.