104-Z-6040
FIBER GLASS FABRIC
PRODUCT DATA

***STYLE* 104 Z-6040**		**US System**	**SI Units**
Type of Yarns	***Warp Yarn:***	ECD 9001/0	
	Fill Yarn:	ECD 1800 1/0	
Fabric Weight, Dry		0.55oz/yd^2	18.6 g/m^2
Weave Style		Plain	

CONSTRUCTION

Nominal Construction	***Warp Count:***	60/in(+/-2)	23.6/cm
	Fill Count:	52/in(+/-2)	20.5./cm
Fabric Thickness		1.0 mils	0.03 mm
Fabric breaking strength	***WARP***	*15 lbf /in*	
	Filling	*6 lbf/in*	

Markets

Applications

IMPORTANT

**The values represent limited tensile data and will be updated via statistically sound data analysis methods.*

All information is believed to be accurate but is given without acceptance of liability. All values have been generated from limited data. The values listed for weight, thickness, and breaking strengths are typical greige values, unless otherwise noted. Users should make their own assessment of the suitability of any product for the purpose required. All sales are made subject to our standard terms of sales which include limitations on liability and other important terms. The fabric style listed may not be available from inventory, and minimum order quantities may apply.

FOR FURTHER INFORMATION, PLEASE CONTACT US

JPS COMPOSITE MATERIALS
A STEEL PARTNERS COMPANY

2200 S. Murray Ave.
Anderson, SC 29622
USA
Phone: 864-225-7028
Fax: 864-260-6581